


D-Line

大前角内螺纹刀片


新




特征及优势

- 管接头行业专用解决方案
- 内螺纹加工排屑效果出色
- 切削力越低, 寿命越好
- 适合大批量生产使用
- 可安装于标准VARDEX螺纹刀杆
- D-Line只有VKX材质可用

内螺纹




公制ISO



标准：R262 (DIN 13)
公差等级：6H

刀片尺寸		螺距	订货代码	尺寸mm			刀垫	刀杆
IC	L mm	mm	RH	h min	X	Y	RH	
1/4"	11	1.0	2DIR1.0ISO...	0.58	0.6	0.7	-	NVR..-2
		1.25	2DIR1.25ISO...	0.72	0.8	0.9		
		1.5	2DIR1.5ISO...	0.87	0.9	1.0		
		2.0	2DIR2.0ISO...	1.15	1.1	0.9		
3/8"	16	1.0	3DIR1.0ISO...	0.58	0.6	0.7	YI3	AVR..-3
		1.5	3DIR1.5ISO...	0.87	0.8	1.0		
		1.75	3DIR1.75ISO...	1.01	0.9	1.2		
		2.0	3DIR2.0ISO...	1.15	1.0	1.3		
		2.5	3DIR2.5ISO...	1.44	1.1	1.5		
1/2"	22	3.0	3DIR3.0ISO...	1.73	1.1	1.5	YI4	AVR..-4
		3.5	4DIR3.5ISO...	2.02	1.6	2.3		
		4.0	4DIR4.0ISO...	2.31	1.6	2.3		


美制UN




标准：ANSI B1.1:74
公差等级：2B

刀片尺寸		螺距	订货代码	尺寸mm			刀垫	刀杆
IC	L mm	TPI	RH	h min	X	Y	RH	
1/4"	11	24	2DIR24UN...	0.61	0.7	0.8	-	NVR..-2
		20	2DIR20UN...	0.73	0.8	0.9		
		18	2DIR18UN...	0.81	0.8	1.0		
3/8"	16	20	3DIR20UN...	0.73	0.8	0.9	YI3	AVR..-3
		16	3DIR16UN...	0.92	0.9	1.1		
		14	3DIR14UN...	1.05	0.9	1.2		
		12	3DIR12UN...	1.22	1.1	1.4		
		8	3DIR8UN...	1.83	1.1	1.5		

内螺纹




惠氏螺纹



标准：B.S.84:1956, DIN 259,
ISO228/1:1982
公差等级：Medium class A

刀片尺寸		螺距	订货代码	尺寸mm			刀垫	刀杆
IC	L mm	TPI	RH	h min	X	Y	RH	
1/4"	11	19	2DIR19W...	0.86	0.8	1.0	-	NVR...-2
3/8"	16	19	3DIR19W...	0.86	0.8	1.0	Y13	AVR...-3
		14	3DIR14W...	1.16	1.0	1.2		
		11	3DIR11W...	1.48	1.1	1.5		


BSPT



标准：B.S. 21:1985
公差等级：标准刀片 BSPT

刀片尺寸		螺距	订货代码	尺寸mm			刀垫	刀杆
IC	L mm	TPI	RH	h min	X	Y	RH	
1/4"	11	19	2DIR19BSPT...	0.86	0.8	0.9	-	NVR...-2
		14	2DIR14BSPT...	1.16	0.9	1.0		
3/8"	16	19	3DIR19BSPT...	0.86	0.8	0.9	Y13	AVR...-3
		14	3DIR14BSPT...	1.16	1.0	1.2		
		11	3DIR11BSPT...	1.48	1.1	1.5		

NPT



标准：USAS B2.1:1968
公差等级：标准刀片 NPT

刀片尺寸		螺距	订货代码	尺寸mm			刀垫	刀杆
IC	L mm	TPI	RH	h min	X	Y		
1/4"	11	18	2DIR18NPT...	1.01	0.7	0.8	-	NVR...-2
		14	2DIR14NPT...	1.33	0.8	1.0		
3/8"	16	18	3DIR18NPT...	1.01	0.8	1.0	Y13	AVR...-3
		14	3DIR14NPT...	1.33	0.9	1.2		
		11.5	3DIR11.5NPT...	1.64	1.1	1.5		